




PVC TUBING

PVC TUBE (TYPE WT-H006 105°C HEAT RESISTANCE)

- Standard : HES 3213Z, GHA-6000 : HARNESS TUBE (PVC)
- Symbol designed the following :
 - PVC : Polyvinyl Tube
 - WT : Willson Tube,
- Rating : 105°C
- Application : PVC Tubing mainly used for electrical insulation
- Construction and Performance:




Size (mm)	Inside Diameter (d) (mm)	Outside Diameter (D) (mm)	Thickness (T)			Length / Coil
			Maximum (mm)	Nominal (mm)	Minimum (mm)	
5.0 x 6.0	5.0 ^{+0.4} _{-0.3}	6.0	0.60	0.50	0.42	300
6.0 x 7.0	6.0 ^{+0.4} _{-0.3}	7.0	0.60	0.50	0.42	300
6.0 x 8.0	6.0 ^{+0.4} _{-0.3}	8.0	1.10	1.00	0.92	200
7.0 x 8.0	7.0 ^{+0.6} _{-0.4}	8.0	0.60	0.50	0.42	200
7.0 x 9.0	7.0 ^{+0.6} _{-0.4}	9.0	1.10	1.00	0.92	200
8.0 x 9.0	8.0 ^{+0.6} _{-0.4}	9.0	0.60	0.50	0.42	200
8.0 x 10.0	8.0 ^{+0.6} _{-0.4}	10.0	1.10	1.00	0.92	200
10.0 x 11.0	10.0 ^{+0.6} _{-0.4}	11.0	0.60	0.50	0.42	200
12.0 x 13.2	12.0 ^{+1.0} _{-0.5}	13.2	0.72	0.60	0.54	200

Marking :

WILSON WT-H006 105°C

PVC TUBE (TYPE WT-G002 60°C GENERAL TUBE)


- Standard : JIS C2410
- Symbol designed the following :
 PVC : Polyvinyl Tube
 WT : Willson Tube,
- Rating : 60°C
- Application : PVC Tubing mainly used for electrical insulation
- Construction and Performance:



Size (mm)	Inside Diameter (d) (mm)	Outside Diameter (D) (mm)	Thickness (T)			Length / Coil
			Maximum (mm)	Nominal (mm)	Minimum (mm)	
5.0 x 6.0	5.0 ^{+0.4} _{-0.3}	6.0	0.60	0.50	0.42	300
6.0 x 7.0	6.0 ^{+0.4} _{-0.3}	7.0	0.60	0.50	0.42	300
6.0 x 8.0	6.0 ^{+0.4} _{-0.3}	8.0	1.10	1.00	0.92	200
7.0 x 8.0	7.0 ^{+0.6} _{-0.4}	8.0	0.60	0.50	0.42	200
7.0 x 9.0	7.0 ^{+0.6} _{-0.4}	9.0	1.10	1.00	0.92	200
8.0 x 9.0	8.0 ^{+0.6} _{-0.4}	9.0	0.60	0.50	0.42	200
8.0 x 10.0	8.0 ^{+0.6} _{-0.4}	10.0	1.10	1.00	0.92	200
10.0 x 11.0	10.0 ^{+0.6} _{-0.4}	11.0	0.60	0.50	0.42	200
12.0 x 13.2	12.0 ^{+1.0} _{-0.5}	13.2	0.72	0.60	0.54	200

PVC TUBE (TYPE WT-T003 60°C GENERAL TUBE)

- Standard : JIS C2410
- Symbol designed the following :
PVC : Polyvinyl Tube
WT : Willson Tube,
- Rating : 60°C
- Application : PVC Tubing mainly used for electrical insulation
- Construction and Performance:



Size (mm)	Inside Diameter (d) (mm)	Outside Diameter (D) (mm)	Thickness (T)			Length / Coil
			Maximum (mm)	Nominal (mm)	Minimum (mm)	
5.0 x 6.0	5.0 ^{+0.4} _{-0.3}	6.0	0.60	0.50	0.42	300
6.0 x 7.0	6.0 ^{+0.4} _{-0.3}	7.0	0.60	0.50	0.42	300
6.0 x 8.0	6.0 ^{+0.4} _{-0.3}	8.0	1.10	1.00	0.92	200
7.0 x 8.0	7.0 ^{+0.6} _{-0.4}	8.0	0.60	0.50	0.42	200
7.0 x 9.0	7.0 ^{+0.6} _{-0.4}	9.0	1.10	1.00	0.92	200
8.0 x 9.0	8.0 ^{+0.6} _{-0.4}	9.0	0.60	0.50	0.42	200
8.0 x 10.0	8.0 ^{+0.6} _{-0.4}	10.0	1.10	1.00	0.92	200
10.0 x 11.0	10.0 ^{+0.6} _{-0.4}	11.0	0.60	0.50	0.42	200
12.0 x 13.2	12.0 ^{+1.0} _{-0.5}	13.2	0.72	0.60	0.54	200